




MATERIAL SAFETY DATA SHEET

1. Product and Company Identification

Product Name Dynamic Wallpaper Remover
Synonym(s) GF150225
CAS # Mixture
Product Use Wallpaper Remover
Manufacturer Dynamic Paint Products Inc.
7040 Financial Drive
Mississauga, ON L5N 7H5 CA
Phone: 1-905-812-9319
Emergency Phone: 1-613-996-6666 (CANUTEC)

LEGEND HMIS/NFPA	
Severe	4
Serious	3
Moderate	2
Slight	1
Minimal	0

Health	/ 2
Flammability	0
Physical Hazard	0
Personal Protection	B



2. Hazards Identification

Emergency Overview WARNING
Eye and skin irritant.

Potential short term health effects

Routes of exposure Eye, Skin contact, Skin absorption, Inhalation, Ingestion.

Eyes May cause irritation.

Skin May cause irritation. May be absorbed through the skin.

NIOSH - Pocket Guide - Skin Notations
Ethylene glycol monobutyl ether 111-76-2 Potential for dermal absorption

Inhalation Harmful if inhaled. May cause respiratory tract irritation.

Ingestion May cause stomach distress, nausea or vomiting.

Target organs Blood. Eyes. Kidney. Liver. Respiratory system. Skin.

Chronic effects Prolonged or repeated exposure can cause drying, defatting and dermatitis.

Signs and symptoms Symptoms may include redness, oedema, drying, defatting and cracking of the skin. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.

3. Composition/Information on Ingredients

Ingredient(s)	CAS #	Percent
Ethylene glycol monobutyl ether	111-76-2	1 - 5

4. First Aid Measures

First aid procedures

Eye contact Flush with cool water. Remove contact lenses, if applicable, and continue flushing. Obtain medical attention if irritation persists.

Skin contact Flush with cool water. Wash with soap and water. Obtain medical attention if irritation persists.

Inhalation If symptoms develop move victim to fresh air. If symptoms persist, obtain medical attention.

Ingestion Do not induce vomiting. Never give anything by mouth if victim is unconscious, or is convulsing. Obtain medical attention.

Notes to physician Symptoms may be delayed.

General advice

If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Avoid contact with eyes and skin. Keep out of reach of children.

5. Fire-fighting Measures

Flammable properties	Not flammable by WHMIS criteria.
Extinguishing media	
Suitable extinguishing media	Dry chemical. Alcohol foam. Carbon dioxide.
Unsuitable extinguishing media	Not available
Protection of firefighters	
Specific hazards arising from the chemical	Not available
Protective equipment for firefighters	Firefighters should wear full protective clothing including self contained breathing apparatus.
Hazardous combustion products	May include and are not limited to: Oxides of carbon.
Explosion data	
Sensitivity to mechanical impact	Not available
Sensitivity to static discharge	Not available

6. Accidental Release Measures

Personal precautions	Keep unnecessary personnel away. Do not touch or walk through spilled material. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Keep people away from and upwind of spill/leak.
Methods for containment	Stop leak if you can do so without risk. Prevent entry into waterways, sewers, basements or confined areas.
Methods for cleaning up	Before attempting clean up, refer to hazard data given above. Small spills may be absorbed with non-reactive absorbent and placed in suitable, covered, labelled containers. Prevent large spills from entering sewers or waterways. Contact emergency services and supplier for advice. Never return spills in original containers for re-use.

7. Handling and Storage

Handling	Use good industrial hygiene practices in handling this material.
Storage	Keep out of reach of children. Store in a closed container away from incompatible materials.

8. Exposure Controls / Personal Protection

Exposure limit values	
Ingredient(s)	Exposure limit values
Ethylene glycol monobutyl ether	ACGIH-TLV TWA: 20 ppm
Engineering controls	Use only under good ventilation conditions or with respiratory protection.
Personal protective equipment	
Eye/Face protection	Wear safety glasses with side shields.
Hand protection	Rubber gloves. Confirm with a reputable supplier first.
Skin and body protection	As required by employer code.
Respiratory protection	Not normally required if good ventilation is maintained and exposure guidelines are not exceeded. Where exposure guideline levels may be exceeded, use an approved NIOSH respirator.
General hygiene considerations	Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. Wash hands before breaks and immediately after handling the product.

9. Physical and Chemical Properties

Appearance	Clear.
-------------------	--------

Colour	Colourless
Form	Liquid
Odour	Mild
Odour threshold	Not available
Physical state	Liquid
pH	6 - 8
Freezing point	Not available
Boiling point	Not available
Pour point	Not available
Flash point	None
Evaporation Rate	Not available
Flammability limits in air, lower, % by volume	Not applicable
Flammability Limits in Air, Upper, % by Volume	Not applicable
Vapour pressure	17.5 mmHg
Vapour density	0.6 (Air = 1)
Specific gravity	1.01 (H2O = 1)
Octanol/water coefficient	Not available
Solubility (H2O)	Complete
Auto-ignition temperature	Not applicable
Viscosity	Water thin
Percent volatile	75 (WT %)

10. Stability and Reactivity

Chemical stability	Stable under recommended storage conditions.
Conditions to avoid	Do not mix with other chemicals.
Incompatible materials	Caustics. Acids. Oxidizers.
Hazardous decomposition products	May include and are not limited to: Oxides of carbon.
Possibility of hazardous reactions	Hazardous polymerisation does not occur.

11. Toxicological Information

Component analysis - LC50

Ingredient(s)	LC50
Ethylene glycol monobutyl ether	2.21 mg/l/4h rat

Component analysis - Oral LD50

Ingredient(s)	LD50
Ethylene glycol monobutyl ether	470 mg/kg rat; 320 mg/kg rabbit

Effects of acute exposure

Eye	May cause irritation.
Skin	May cause irritation. May be absorbed through the skin.

NIOSH - Pocket Guide - Skin Notations

Ethylene glycol monobutyl ether 111-76-2 Potential for dermal absorption

Inhalation Harmful if inhaled. May cause respiratory tract irritation.

Ingestion May cause stomach distress, nausea or vomiting.

Sensitisation Non-hazardous by WHMIS criteria.

Chronic effects Non-hazardous by WHMIS criteria.

Carcinogenicity Non-hazardous by WHMIS criteria.

ACGIH - Threshold Limit Values - Carcinogens

Ethylene glycol monobutyl ether 111-76-2 A3 - Confirmed animal carcinogen with unknown relevance to humans.

IARC - Group 3 (Not Classifiable)

Ethylene glycol monobutyl ether 111-76-2 Monograph 88 [2006]

Mutagenicity	Non-hazardous by WHMIS criteria.
Reproductive effects	Non-hazardous by WHMIS criteria.
Teratogenicity	Non-hazardous by WHMIS criteria.
Synergistic Materials	Not available

12. Ecological Information

Ecotoxicity	Components of this product have been identified as having potential environmental concerns.	
Ecotoxicity - Freshwater Fish Species Data		
Ethylene glycol monobutyl ether	111-76-2	96 Hr LC50 Lepomis macrochirus: 1490 mg/L [static]; 96 Hr LC50 Lepomis macrochirus: 2950 mg/L
Ecotoxicity - Water Flea Data		
Ethylene glycol monobutyl ether	111-76-2	24 Hr EC50 Daphnia magna: 1698 - 1940 mg/L; 48 Hr EC50 Daphnia magna: >1000 mg/L
Environmental effects	Not available	
Aquatic toxicity	Not available	
Persistence and degradability	Not available	
Bioaccumulation/accumulation	Not available	
Partition coefficient	Not available	
Mobility in environmental media	Not available	
Chemical fate information	Not available	
Other adverse effects	Not available	

13. Disposal Considerations

Waste codes	Not available
Disposal instructions	Review federal, provincial, and local government requirements prior to disposal.
Waste from residues / unused products	Not available
Contaminated packaging	Not available

14. Transport Information

Transportation of Dangerous Goods (TDG - Canada)	Not regulated as dangerous goods.
---	-----------------------------------

15. Regulatory Information

Canadian federal regulations	This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.	
Canada - CEPA - Schedule I - List of Toxic Substances		
Ethylene glycol monobutyl ether	111-76-2	Present
Canada - WHMIS - Ingredient Disclosure List		
Ethylene glycol monobutyl ether	111-76-2	1 %
WHMIS classification	Class D - Division 2B	
WHMIS status	Controlled	
WHMIS labeling		



Inventory Status

Country(s) or region	Inventory Name	On Inventory (Yes/No)*
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No

A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

16. Other Information

Disclaimer	Information contained herein was obtained from sources considered technically accurate and reliable. While every effort has been made to ensure full disclosure of product hazards, in some cases data is not available and is so stated. Since conditions of actual product use are beyond control of the supplier, it is assumed that users of this material have been fully trained according to the requirements of all applicable legislation and regulatory instruments. No warranty, expressed or implied, is made and supplier will not be liable for any losses, injuries or consequential damages which may result from the use of or reliance on any information contained in this document.
Issue date	08-Jan-2010
Effective Date	28-Feb-2010
Expiry Date	28-Feb-2013
Prepared by	Dell Tech Laboratories Ltd. (519) 858-5021
Other Information	For an updated MSDS, please contact the supplier/manufacturer listed on the first page of the document.